

## ATTIC CARD

## THIS IS PROCELL GREEN TYPE 1 CELLULOSE LOOSE FILL INSULATION

Application Coverage Chart				25 lbs (11.3 kg)					ProCell Green			
Thermal	Thermal Resistance		Applied Thickness		Settled Thickness		Mass per Unit Area		Coverage Per Bag		# Bags Required	
RSI	R Value	mm	In (po)	mm	In (po)	kg/m <sup>2</sup>	lb/ft <sup>2</sup> (lb/p <sup>2</sup> )	m²	ft <sup>2</sup> (pi <sup>2</sup> )	100 m <sup>2</sup>	1000 ft <sup>2</sup> (pi <sup>2</sup> )	
1.8	10	74.9	2.9	67	2.6	1.71	0.35	6.6	71.3	15.1	14.0	
3.5	20	149.7	5.9	134	5.3	3.43	0.70	3.3	35.6	30.2	28.1	
5.3	30	224.6	8.8	201	7.9	5.14	1.05	2.2	23.8	45.3	42.1	
7.1	40	299.5	11.8	267	10.5	6.85	1.40	1.7	17.8	60.4	56.1	
8.8	50	374.3	14.7	334	13.2	8.56	1.75	1.3	14.3	75.5	70.2	
10.6	60	449.2	17.7	401	15.8	10.28	2.11	1.1	11.9	90.6	84.2	
12.3	70	524.0	20.6	468	18.4	11.99	2.46	0.9	10.2	105.8	98.2	
14.1	80	598.9	23.6	535	21.1	13.70	2.81	0.8	8.9	120.9	112.3	
15.9	90	673.8	26.5	602	23.7	15.42	3.16	0.7	7.9	136.0	126.3	
17.6	100	748.6	29.5	668	26.3	17.13	3.51	0.7	7.1	151.1	140.4	

R-VALUE 3.8/in (RSI 0.0263/mm)

DESIGN DENSITY 1.6 lbs/ft3 (25.6 kg/m3)Coverage per bag for wood framing includes a 10% correction factor (positive)

These charts represent average machine applied coverages which may be affected according to equipment and applicators' techniques. From R-40 or RSI-7.0, it may be necessary to bring a correction according to the application technique. Coverage table values are based on 11.3 KG / 25 LBS nominal bag weight.

TYPE 1 (WALLS)					25	lbs (11.3 kg)	ProCell Green		
Thermal I	Thermal Resistance Framing (Wood) Ma		Mass per	Unit Area	Coverage Per Bag		# Bags Required		
RSI	R Value	mm	In (po)	kg/m <sup>2</sup>	lb/ft <sup>2</sup> (lb/p <sup>2</sup> )	m2	ft <sup>2</sup> (pi <sup>2</sup> )	100 m <sup>2</sup>	1000 ft <sup>2</sup> (pi <sup>2</sup> )
2.3 3.6	12.8 20.2	38 x 89 38 x 140	2x4 2x6	3.7 5.9	0.8 1.2	3.0 1.9	32.3 20.8	33.0 52.0	31.0 48.0

For new construction, insulation must be installed in accordance to manufactures EnviroShield system specifications. Coverages are based on 16 inch (406 mm) centre construction. (CCMC Material Evaluation Report #12420R).

ProCell Green provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, ProCell Green Insulation is specially treated for flame resistance.

R-value means resistance to heat flow-the higher the R-value, the greater the insulation power.

CERT	IF.	ICAT	ION:

This insulation has been installed in conformance with the above
recommendations, to provide a value of R using bags
of this insulation to cover square feet of area.
Builder's Signature:
Company Name:
Date:
Applicator's Signature:
Company Name:
Date:

## Manufacturer's Warranty

Greenfiber warrants that ProCell Insulation is manufactured to meet or exceed product standards CAN/ULC-S703 and ASTM C-739.

ProCell Insulation is guaranteed to provide the thermal performance indicated above for the normal life of the building, provided the material is installed according to manufacturer's instructions. The liability of Greenfiber will be limited to the replacement of defective insulation or installation of additional insulation provided a copy of this completed card and proof of purchase is supplied to Greenfiber.

In no event shall Greenfiber be responsible or liable for any damages resulting from the use or misuse or installation of the product, whether such damage is direct, indirect, consequential or otherwise. This warranty excludes all damages to the insulation resulting from defects or deterioration in the structure, physical or mechanical abuse and or acts of nature.

Manufactured by Greenfiber

Toll-Free 800-228-0024 www.greenfiber.com

Greenfiber is a registered trademark of Greenfiber
© 2023 Greenfiber. All rights reserved.

Greenfiber 5500 77 Center Drive, Suite 100

Charlotte, NC 28217

Debert, Nova Scotia
Casa Grande, AZ 85193
Chandler, AZ 85225
Decatur, AL 35601
Tampa, FL 33605
Eastanollee, GA 30538
Hickory, KY 42051
Springfield, KY 40069
Webberville, MI 48892
Lester Prairie, MN 55354
Norfolk, NE 68701
Chambersburg, PA 17201
Wilkes Barre, PA 18702
Waco, TX 76704
Salt Lake City, UT 84119

